


# BAG FILTERS

## NW



### APPLICATIONS

Primary filtration for air treatment units.

### ADVANTAGES

- Low pressure drop
- Excellent dust holding capacity
- Self-supporting welded pocket
- Easy to place
- Tested for food contact according to CE 1935/2004

### GENERAL FEATURES

- Efficiency following ISO 16890 : 2016
- Media: Nanowave
- Final pressure drop: 300 Pa
- Maximum T° in continuous service: 80°C
- Humidity: 100% RH

Barcode	Description	Width A (mm)	Height B (mm)	Depth C (mm)	Pocket	Media area (m <sup>2</sup> )	Flow rate (m <sup>3</sup> /h)/ Delta P (Pa)	Energy cons. (kWh/an) *	Energy class **
<b>M6 - ePM10 55% ISO 16890</b>									
1718662	NW65-6/635/10	592	592	635	10	7,5	3400 / 47	582	B
1718350	NW65-5/635/08	490	592	635	8	6,0	2800 / 47	-	-
1718352	NW65-3/635/05	287	592	635	5	3,8	1700 / 47	-	-
1718870	NW65-6/635/08	592	592	635	8	6,00	3400 / 48	770	B
1718332	NW65-5/635/06	490	592	635	6	4,50	2800 / 48	-	-
1718334	NW65-3/635/04	287	592	635	4	3,00	1700 / 48	-	-
1718852	NW65-6/535/10	592	592	535	10	6,30	3400 / 50	631	B
1719244	NW65-5/535/08	490	592	535	8	5,0	2800 / 50	-	-
1719243	NW65-3/535/05	287	592	535	5	3,20	1700 / 50	-	-
1718873	NW65-6/535/08	592	592	535	8	5,10	3400 / 50	650	B
1718338	NW65-5/535/06	490	592	535	6	3,80	2800 / 50	-	-
1718340	NW65-3/535/04	287	592	535	4	2,50	1700 / 50	-	-
<b>F7 - ePM1 50% ISO 16890</b>									
1728358	NW80-6/635/10	592	592	635	10	7,5	3400 / 80	1047	B
1728312	NW80-5/635/08	490	592	635	8	6,0	2800 / 80	-	-
1728359	NW80-3/635/05	287	592	492	5	3,8	1700 / 80	-	-
1728404	NW80-6/635/08	592	592	635	8	6,00	3400 / 92	1295	C
1729029	NW80-5/635/06	490	592	635	6	4,5	2800 / 92	-	-
1728404	NW80-3/635/04	287	592	635	4	3,00	1700 / 92	-	-
1728406	NW80-6/535/10	592	592	535	10	6,30	3400 / 100	1396	C
1728311	NW80-5/535/08	490	592	535	8	5,10	2800 / 100	-	-
1729028	NW80-3/535/05	287	592	535	5	3,20	31700 / 100	-	-
<b>F7 - ePM1 60% ISO 16890</b>									
1717554	NW85-6/635/08	592	592	635	8	6	3400 / 74	950	A
1718293	NW85-5/635/06	490	592	635	6	4,50	2800 / 74	-	-
1719406	NW85-3/635/04	287	592	635	4	3	1700 / 74	-	-
1717556	NW85-6/635/10	592	592	635	10	7,5	3400 / 74	945	A
1721331	NW85-5/635/08	490	592	635	8	6,00	2800 / 74	-	-
1720021	NW85-3/635/05	287	592	635	5	3,8	1700 / 74	-	-
1717556	NW85-6/535/10	592	592	535	10	6,30	3400 / 74	946	A
1719246	NW85-5/535/08	490	592	535	8	5,10	2800 / 74	-	-
1719164	NW85-3/535/05	287	592	535	5	3,20	1700 / 74	-	-
1717553	NW85-6/535/08	592	592	535	8	5,10	3400 / 85	1254	C
1718298	NW85-5/535/06	490	592	535	6	3,80	2800 / 85	-	-
1718300	NW85-3/535/04	287	592	535	4	2,50	1700 / 85	-	-

\* Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

\*\* Energy class: according to Eurovent RS 4/C/001-2019



# BAG FILTERS

## NW

Barcode	Description	Width A (mm)	Height B (mm)	Depth C (mm)	Pocket	Media area (m <sup>2</sup> )	Flow rate (m <sup>3</sup> /h)/ Delta P (Pa)	Energy cons. (kwh/an) *	Energy class **
<b>F8 - ePM1 70% ISO 16890</b>									
1719493	NW95-6/635/10	592	592	635	10	7,5	3400 / 74	936	A+
1719976	NW95-5/635/08	490	592	635	8	6,0	2800 / 74	-	-
1719977	NW95-3/635/05	287	592	635	5	3,8	1700 / 74	-	-
1719491	NW95-6/635/08	592	592	635	8	6	3400 / 81	1067	A
1719978	NW95-5/635/06	490	592	635	6	4,50	2800 / 81	-	-
1719979	NW95-3/635/04	287	592	635	4	3	1700 / 81	-	-
1719150	NW95-6/535/10	592	592	535	10	6,30	3400 / 81	1056	A
1719973	NW95-5/535/08	490	592	535	8	5,10	2800 / 81	-	-
1719148	NW95-3/535/05	287	592	535	5	3,20	1700 / 81	-	-
<b>F9 - ePM1 90% ISO 16890</b>									
1717565	NW98-6/635/10	592	592	635	10	7,5	3400 / 118	1392	A
1719983	NW98-5/635/08	490	592	635	8	6,0	2800 / 118	-	-
1719511	NW98-3/635/05	287	592	635	5	3,8	1700 / 118	-	-
1717561	NW98-6/635/08	592	592	635	8	6	3400 / 119	1397	A
1719984	NW98-5/635/06	490	592	635	6	4,50	2800 / 119	-	-
1719334	NW98-3/635/04	287	592	635	4	3	1700 / 119	-	-
1717563	NW98-6/535/10	592	592	535	10	6,30	3400 / 147	1837	C
1719980	NW98-5/535/08	490	592	535	8	5,10	2800 / 147	-	-
1719147	NW98-3/535/05	287	592	535	5	3,20	1700 / 147	-	-
1717559	NW98-6/535/08	592	592	535	8	5,10	3400 / 155	2001	D
1719981	NW98-5/535/06	490	592	535	6	3,80	2800 / 155	-	-
1719982	NW98-3/535/04	287	592	535	4	2,50	1700 / 155	-	-



**Tip** 💡 Energy saver champion (class A) and long lifetime

