


# BAG FILTERS

K+



Barcode Description Width A (mm) Height B (mm) Depth C (mm) Pocket Media area (m<sup>2</sup>) Flow rate (m<sup>3</sup>/h)/ Delta P (Pa) Energy cons. (Kwh/an) \* Energy class \*\*

## F7 - ePM2,5 70% ISO 16890

Barcode	Description	Width A (mm)	Height B (mm)	Depth C (mm)	Pocket	Media area (m <sup>2</sup> )	Flow rate (m <sup>3</sup> /h)/ Delta P (Pa)	Energy cons. (Kwh/an) *	Energy class **
1716541	K+85-6/635/10	592	592	635	10	7,50	3400 / 90	1546	D
1720824	K+85-5/635/08	490	592	635	8	6,00	2800 / 90	-	-
1717362	K+85-3/635/05	287	592	635	5	3,80	1700 / 90	-	-
1716540	K+85-6/635/08	592	592	635	8	6,00	3400 / 110	1634	D
1720823	K+85-5/635/06	490	592	635	6	4,50	2800 / 110	-	-
1717361	K+85-3/635/04	287	592	635	4	3,00	1700 / 110	-	-
1716539	K+85-6/635/06	592	592	635	6	4,50	3400 / 116	1995	D
1720822	K+85-5/635/05	490	592	625	5	3,80	2800 / 116	-	-
1720826	K+85-3/635/03	287	592	635	3	2,30	1700 / 116	-	-
1716538	K+85-6/535/08	592	592	535	8	5,10	3400 / 120	2011	E
1720821	K+85-5/535/06	490	592	535	6	3,80	2800 / 120	-	-
1717360	K+85-3/535/04	287	592	535	4	2,50	1700 / 120	-	-
1716537	K+85-6/535/06	592	592	535	6	3,80	3400 / 136	2214	E
1720819	K+85-5/535/05	490	592	535	5	3,20	2800 / 136	-	-
1720825	K+85-3/535/03	287	592	535	3	1,9	1700 / 136	-	-

\* Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

\*\* Energy class: according to Eurovent RS 4/C/001-2019

## APPLICATIONS

Filtration for air treatment units.

## ADVANTAGES

- HIGH-TECH aerodynamic profile reducing turbulences in the outlet air
- Conical sewn pocket
- Low pressure drop
- Tested for food contact according to CE 1935/2004

## GENERAL FEATURES

- Efficiency following ISO 16890 : 2016
- Media: Synthetic
- Final pressure drop: 300 Pa
- ECO recommended final pressure drop: 250 Pa
- Maximum T° in continuous service: 70°C
- Humidity: 100% RH



Tip 💡 Synthetic filter new generation meets the EN779:2012. Ask the VTT or SP test..

